

AlphaServer 800 5/500 Systems

| Order number | Operating system | Server systems, 64bits 500MHz | | | | | |
|--------------|------------------|-------------------------------|-------|-------|-------|----|------|
| #1 | PB82B-FA | DIGITAL UNIX | 128MB | 4.3GB | CD,RX | NI | SVGA |
| | PB82B-FB | DIGITAL UNIX | 256MB | 4.3GB | CD,RX | NI | SVGA |
| | PB82B-FC | DIGITAL UNIX | 512MB | 4.3GB | CD,RX | NI | SVGA |
| | PB82B-FD | DIGITAL UNIX | 1GB | 4.3GB | CD,RX | NI | SVGA |
| | PB82B-MA | OpenVMS | 128MB | 4.3GB | CD,RX | NI | SVGA |
| | PB82B-MB | OpenVMS | 256MB | 4.3GB | CD,RX | NI | SVGA |
| | PB82B-MC | OpenVMS | 512MB | 4.3GB | CD,RX | NI | SVGA |
| | PB82B-MD | OpenVMS | 1GB | 4.3GB | CD,RX | NI | SVGA |

↑ B/P = Pedestal/Rackmount

#2 SVGA color monitor #3 For 240V use, select power cord and keyboard.

15" SN-PCXBV-EZ/EY
17" SN-PCXBV-FZ/FY
21" SN-PCXAV-WZ/WY
North/South

| | | | |
|--------|--------|--------|-------|
| LK97W- | -AE GB | -AG G | -AM S |
| UNIX | -AB B | -AH NL | -AN N |
| | -AD DK | -AI I | -AP F |
| LK46W- | -AF FI | -AK CH | -AS E |
| OVMS | | | |

BN19C-2E Europe
BN19A-2E GB
BN19E-2E CH
BN19K-2E DK
BN19Z-2E I

Internal options

Memory expansion

| | | |
|----------|-------|-----------------------------|
| PB8MA-AC | 64MB | Max memory: 2x 1GB = 2GB |
| PB8MA-AD | 128MB | |
| PB8MA-AE | 256MB | |
| PB8MA-AF | 512MB | |
| PB8MA-AG | 1GB | |

System

128 MB

Internal storage

Tape storage

| | |
|----------|------------------------|
| PBXTZ-AA | 2.0GB Qick tape drive |
| TLZ09-LK | 8.0GB DAT tape drive |
| TLZ10-LK | 12/24GB DAT tape drive |

Disk storage

| | |
|----------|--------------------------|
| RZ1BB-SB | 2.1GB UltraSCSI SCA disk |
| RZ1CB-SB | 4.3GB UltraSCSI SCA disk |
| RZ1DB-SB | 9.0GB UltraSCSI SCA disk |

| | |
|----------|---------------------------------|
| KZPBA-CA | UltraSCSI SE adapter |
| BN38C-02 | 2m SCSI cable,68HD-VHDCI |
| KZPAC-AA | RAID 1-port, 4MB cache |
| KZPAC-CB | RAID 3-port, 8MB cache |
| KZPSC-UB | Cache battery |
| KZPAC-SB | Dual cable bulkhead |
| BN37A-02 | 2m SCSI cbl VHDCI-VHDCI |
| PB8HA-DA | SCSI cable for internal storage |

Controllers

| | |
|----------|-------------------------|
| DE500-AA | Fast Ethernet 10/100 |
| DE450-CA | Ethernet,thin/thic/twis |
| DEFPA-AB | FDDI adapter,SAS MMF |
| DEFPA-DB | FDDI adapter,DAS MMF |
| DEFPA-UB | FDDI adapter,SAS TP-PMD |
| KFP5A-AA | DSSI controller |
| PBXNP-AA | Token ring adapter |



External options

Tape storage

| | |
|-------------|----------------------|
| DS-TZ89N-TA | 35/70GB DLT tape,TT |
| BN21K-02 | SCSI cable, FWD |
| BN19C-2E | Power cord, Europe |
| KZPDA-AA | SCSI controller,FWSE |

Disk storage

| | |
|-------------|----------------------|
| DS-BA356-KF | Pedestal, single bus |
| DS-BA356-KG | Pedestal, split bus |
| BN37A-02 | 2m SCSI,VHDCI-VHDCI |
| BN19C-2E | Power cord, Europe |
| DS-RZ1BB-VW | 2.1GB UltraSCSI disk |
| DS-RZ1CB-VW | 4.3GB UltraSCSI disk |
| DS-RZ1DB-VW | 9.0GB UltraSCSI disk |



Licenses included:

- DIGITAL UNIX V4.0d, Base license, Unlimited User license, Server Extension license, and Internet Access Software license and Netscape's Enterprise Server 3.0.
- OpenVMS V7.1-1H1, Base license and DIGITAL Enterprise Integration Package.

@500MHz
SPECint95 14.2
SPECfp95 16.1
SPECweb96 1158
TPC

Software Processor Code: E

digital 18-May-1998 GEA082
<http://www.digital.com/golden-eggs>

AlphaServer 800 5/500 Systems
GOLDEN EGGS Visual Configurations, Helsinki